

Refine Search

Search Results -

Terms	Documents
6154559.pn. or 6120461.pn. or 5570698.pn.	3

Database:

US Pre-Grant Publication Full-Text Database
 US Patents Full-Text Database
 US OCR Full-Text Database
 EPO Abstracts Database
 JPO Abstracts Database
 Derwent World Patents Index
 IBM Technical Disclosure Bulletins

Search:

10/605637



Search History

DATE: Sunday, June 10, 2007
 [Purge Queries](#)
 [Printable Copy](#)
 [Create Case](#)

Set Name Query

side by side

Hit Count Set Name

result set

DB=USPT; THES=ASSIGNEE; PLUR=YES; OP=OR

L7 6154559.pn. or 6120461.pn. or 5570698.pn. 3 L7

DB=PGPB,USPT; THES=ASSIGNEE; PLUR=YES; OP=OR

L6 l1 and (head with orientation).clm. 31 L6

L5 L3 not L4 29 L5

L4 L3 and 701/\$.ccls. 4 L4

L3 L2 and (vehicle\$ or car\$ or automobile\$) 33 L3

L2 l1 and ((eye\$ and head\$) same orient\$) 60 L2

L1 (eye\$ and head\$ and orient\$ and driv\$.clm. 190 L1

END OF SEARCH HISTORY

[First Hit](#)[Previous Doc](#)[Next Doc](#)[Go to Doc#](#)

Generate Collection

Print

L46: Entry 1 of 3

File: DWPI

Apr 28, 2005

DERWENT-ACC-NO: 2005-401886

DERWENT-WEEK: 200541

COPYRIGHT 2007 DERWENT INFORMATION LTD

TITLE: Unmanned aerial vehicle navigating method, involves reading starting position of vehicle from receiver on vehicle, and piloting vehicle from starting position to waypoint, based on navigation algorithm

INVENTOR: BODIN, W K; REDMAN, J J W ; THORSON, D C

PATENT-ASSIGNEE: INT BUSINESS MACHINES CORP (IBMC)

PRIORITY-DATA: 2003US-0692169 (October 23, 2003)

Search Selected

Search ALL

Clear

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE	PAGES	MAIN-IPC
<input type="checkbox"/> <u>US 20050090972 A1</u>	April 28, 2005		030	G01C021/00

APPLICATION-DATA:

PUB-NO	APPL-DATE	APPL-NO	DESCRIPTOR
US20050090972A1	October 23, 2003	2003US-0692169	

INT-CL (IPC): G01C 21/00

ABSTRACTED-PUB-NO: US20050090972A

BASIC-ABSTRACT:

NOVELTY - The method involves receiving a user's selection of a map pixel representing a waypoint for unmanned aerial vehicle (UAV) navigation, at a remote control device. The pixel is mapped to waypoint coordinates, and the waypoint is transmitted to the UAV. A starting position of the UAV, is read from a GPS receiver on the UAV, and the UAV is piloted from the starting position to the waypoint, based on a navigation algorithm.

DETAILED DESCRIPTION - INDEPENDENT CLAIMS are also included for the following:

(A) a UAV navigating system comprising a global positioning system (GPS) receiver and remote control device

(B) a computer program product for navigating a UAV.

USE - Used for navigating an unmanned aerial vehicle (UAV).ADVANTAGE - The UAV is piloted from the starting position to the waypoint, based on

a navigation algorithm, hence enabling the operators to efficiently control the manual operation of the UAV.

DESCRIPTION OF DRAWING(S) - The drawing shows a flow chart for navigating a UAV.

ABSTRACTED-PUB-NO: US20050090972A

EQUIVALENT-ABSTRACTS:

CHOSEN-DRAWING: Dwg.4/15

DERWENT-CLASS: S02 T01 W05 W06

EPI-CODES: S02-B08G; T01-J07D3; T01-J12B; T01-S03; W05-D06G5; W05-D07D; W05-D08C;
W06-A03A5C; W06-B01B1;

[Previous Doc](#)

[Next Doc](#)

[Go to Doc#](#)

[First Hit](#)[Previous Doc](#)[Next Doc](#)[Go to Doc#](#)

Generate Collection

Print

L46: Entry 2 of 3

File: DWPI

Oct 31, 2006

DERWENT-ACC-NO: 2005-401885

DERWENT-WEEK: 200672

COPYRIGHT 2007 DERWENT INFORMATION LTD

TITLE: UAV navigating method, involves calculating heading based upon starting point, waypoint coordinates and navigation algorithm, identifying flight control instructions on heading, and transmitting instructions to UAV

INVENTOR: BODIN, W K; REDMAN, J J W ; THORSON, D C

PATENT-ASSIGNEE: INT BUSINESS MACHINES CORP (IBMC)

PRIORITY-DATA: 2003US-0692118 (October 23, 2003)

Search Selected

Search ALL

Clear

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE	PAGES	MAIN-IPC
<input type="checkbox"/> <u>US 7130741 B2</u>	October 31, 2006		000	G01C021/28
<input type="checkbox"/> <u>US 20050090945 A1</u>	April 28, 2005		031	G01C021/00

APPLICATION-DATA:

PUB-NO	APPL-DATE	APPL-NO	DESCRIPTOR
US 7130741B2	October 23, 2003	2003US-0692118	
US20050090945A1	October 23, 2003	2003US-0692118	

INT-CL (IPC): G01C 21/00; G01C 21/28

ABSTRACTED-PUB-NO: US20050090945A

BASIC-ABSTRACT:

NOVELTY - The method involves receiving a user's selection of a graphical user interface map pixel in a remote control device e.g. mobile telephone (110). A heading is calculated based upon starting point received from a global position system receiver on a UAV (100), coordinates of waypoint and a navigation algorithm. Flight control instructions are identified on the heading and transmitted from the remote control device to the UAV.

DETAILED DESCRIPTION - INDEPENDENT CLAIMS are also included for the following:

(A) a system for navigating a UAV(B) a computer program product for navigating a UAV.USE - Used for navigating a UAV.

ADVANTAGE - The method automatically navigates the UAV with a single keystroke or mouseclick from operator.

DESCRIPTION OF DRAWING(S) - The drawing shows components of a UAV navigating system.

UAV 100

Workstation 104

Mobile telephone 110

Laptop computer 116

Satellites 190, 192

ABSTRACTED-PUB-NO: US20050090945A
EQUIVALENT-ABSTRACTS:

CHOSEN-DRAWING: Dwg.1/15

DERWENT-CLASS: S02 T01 W05 W06
EPI-CODES: S02-B08G; T01-J07D3; T01-J12B; T01-S03; W05-D06G5; W05-D07D; W05-D08C;
W06-B01B1;

[Previous Doc](#)

[Next Doc](#)

[Go to Doc#](#)